

*Auto Temperature compensation, mV (ORP)
Auto calibration, easy operation, economical type*

pH METER

Model : PH-209B

ISO-9001, CE, IEC1010



pH electrode (optional)



LUTRON ELECTRONIC

The Art of Measurement

pH, ORP/mV, auto calibration

pH METER

Model : PH-209B

FEATURES

* Professional pH/mV METER. pH range : 0 to 14 pH x 0.01 pH. mV range : -1000 mV to 1000 mV.
* The instrument is with mV (millivolt) function for mV measurement (cooperate with optional ORP probe to be a professional ORP meter)
* Wide range manual temperature compensation adjustment .
* Optional ATC (Automatic Temp. Compensation) probe is available for pH measurement.
* Internal Temp. unit °C or °F selection.
* pH function with high input impedance avoids measuring error.
* Microprocessor circuit assures high accuracy and reliable performance.
* Large LCD, dual function display.
* Records Maximum and Minimum readings with recall.
* Data hold.
* Auto power shut off to battery life or manual power off.
* Powered by 006P DC 9V battery.
* Easy and automatic pH calibration procedures.
* Using the durable, long-lasting components and a strong lightweight ABS-plastic housing case.
* Wide applications: water conditioning, aquariums, beverage, fish hatcheries, food processing, photography, laboratory, paper industry, plating industry, quality control, school & college.

GENERAL SPECIFICATIONS

Circuit	Custom one-chip of microprocessor LSI circuit.	
Display	40 mm x 32 mm LCD (Liquid crystal display).	
Measurement	pH	0 to 14 pH
	mV	-1000 mV to 1000 mV
Input Impedance	10 ¹² ohm	
Temperature Compensation for pH measurement	Manual	0 to 100 °C, be adjusted by push button on front panel.
	Automatic (ATC)	* Cooperate the optional Temp. probe, TP-07. * 0 to 65 °C.
pH Calibration	pH 7, pH 4, and pH 10, 3 points calibration ensure the best linearity and accuracy.	

Data hold	Hold the current reading value on the display.
Memory Recall	Maximum and Minimum reading values can be saved and retrieved by record function.
Sampling Time	Approx. 1 second.
Power off	Auto shut off saves battery life or manual off by push button.
Overload indication	"- - -" symbol on the display.
pH Electrode	Optional, Any pH electrode with BNC connector.
Operating Temperature	0 °C to 50 °C (32 °F to 122 °F).
Operating Humidity	Max. 80% RH.
Power Supply	DC 9V battery, 006P, MN1604 (PP3) or equivalent. * <i>Alkaline or heavy duty type.</i>
Power Consumption	Approx. DC 4.5 mA.
Weight	362 g/0.8 LB (battery included).
Dimension	170 x 70 x 39 mm (6.7 x 2.8 x 1.5 inch).
Standard Accessories	Instruction manual.....1 PC.
Optional Probes & Accessories (Ref. page 20)	pH electrodes : * <i>General purpose pH electrode, PE-03</i> * <i>General purpose pH electrode, PE-11</i> * <i>Professional pH electrode, PE-01</i> * <i>Plane pH electrode, PE-08</i> * <i>Glass body heavy duty pH electrode, PE-02</i> * <i>Spear tip pH electrode, PE-04HD, PE-06HD</i> * <i>pH electrode build in Temp. sensor, PE-05T</i> * <i>pH electrode + Temp. probe, kit, PE-03K7</i> ATC probe (Automatic temp. probe), TP-07 ORP electrode, ORP-14 Hard carrying case, CA-06 Soft carrying case, CA-05A

ELECTRICAL SPECIFICATIONS (23 ± 5 °C)

Measurement	Range	Resolution	Accuracy
pH	0 to 14 pH	0.01 pH	± (0.02 pH + 2 d)
mV	0 to ± 1000 mV	1 mV	± (0.5% + 2 d)
* <i>pH accuracy is based on calibrated meter only.</i>			
* <i>Specification tests under the environment RF Field Strength less than 3 V/M & frequency less than 30 MHz only.</i>			