

# TYPE K

# TEMPERATURE PROBE

Model : TP-01, TP-02A, TP-03, TP-04

*ISO-9001, CE, IEC1010*



TP-01



TP-02A



TP-03



TP-04



**LUTRON ELECTRONIC**



*The Art of Measurement*

# TYPE K TEMPERATURE PROBE

Model : TP-01, TP-02A, TP-03, TP-04

<i>Type K PROBE Model</i>	<i>Measurement Range</i>	<i>Accuracy</i>
(Type K) TP-01	<ul style="list-style-type: none"> <li>* Max. short-term operating Temperature: 300 °C (572 °F).</li> <li>* It is an ultra fast response naked-bead thermocouple suitable for many general purpose application.</li> </ul>	± 0.4 %
Thermocouple Probe (Type K), TP-02A	<ul style="list-style-type: none"> <li>* Measure Range: -50 °C to 900 °C , -50 °F to 1650 °F.</li> <li>* Dimension: 10cm tube, 3.2mm Dia.</li> </ul>	± 0.75 %
Thermocouple Probe (Type K), TP-03	<ul style="list-style-type: none"> <li>* Measure Range: -50 °C to 1200 °C , -50 °F to 2200 °F.</li> <li>* Dimension: 10cm tube, 8mm Dia.</li> </ul>	± 0.4 %
Surface Probe (Type K), TP-04	<ul style="list-style-type: none"> <li>* Measure Range: -50 °C to 400 °C , -50 °F to 752 °F.</li> <li>* Size : Temp. sensing head - 15 mm Dia. Probe length - 120 mm.</li> </ul>	± ( 0.75 % +0.5 °C )

\* Appearance and specifications listed in this brochure are subject to change without notice.

0807-TP-01, TP-02A, TP-03, TP-04